

STANDARD SIZES:

12" x 24"	14" x 20"	14" x 24"	14" x 25"	14" x 30"	15" x 20"
16" x 18"	16" x 20"	16" x 21"	16" x 24"	16" x 25"	18" x 20"
20" x 20"	20" x 21"	20" x 24"	20" x 25"	24" x 24"	24" x 30"
25" x 25"					

CUSTOM SIZES ALSO AVAILABLE

SPECIFICATIONS


Pressure drop: 0.09 in.w.c. @ 300 fpm
Arrestance: 93% average arrestance
Dust holding capacity: 150 Grams
Warranty: lifetime

LOW PRESSURE DROP SAVES MONEY!

All filters restrict air flow. The degree of restriction is measured as "pressure drop" and will determine how long and how hard a fan motor will need to operate to achieve the desired heating or cooling level in your home. Therefore selecting a low pressure drop filter will **significantly reduce annual electrical, heating and cooling costs.** Reduce your pressure drop with our model Airtscreen 500.



3-stage washable media

booster 6000/6500

BENEFITS:

- BOOSTS EFFICIENCY** of the airtscreen air cleaners.
- MAINTENANCE FREE**
- 5 YEAR WARRANTY**

HOW IT WORKS:
 Once installed upstream from any air filter, the Airtscreen Booster emits ions that safely and effectively charge airborne particles making them more attracted to the filter. The Booster will increase the efficiency of any air cleaner by 15% within the most harmful particle size range of 0.3 to 1.0 microns. In addition, the Airtscreen Booster requires no maintenance or replacement parts once it has been properly installed within the HVAC system.

SPECIFICATIONS

Nominal input voltage: 24 Volts
Input voltage range: 18 V min to 30 V max
Power consumption: <2 watts
Input type: floating
Optimal booster installation: 8"-16" upstream from center of filter (including elbow or transition in the system)
Operating coverage (per enhancer): 4-9 sq. ft.
Filtration boost: +15% average filtration efficiency (0.3 - 1.0 micron size range)
Dimensions: 1.1" diameter tube by 9" long casing
Warranty: 5 years